



solis

ORCHARD & VINEYARD *Specialist*



N75

ORCHARD & VINEYARD Specialist



FEATURES		N75
ENGINE		
No. of cylinders / capacity (cc) / emissions level	4/ 4088/ Stage V	
After Treatment System	DOC + DPF	
Rated Engine Power (kw/Hp)	54.83/ 73.47	
Rated Engine Speed	2000	
Max. Torque (Nm)	340Nm @ 1400 Rpm	
Aspiration	Turbo charged with Intercooler	
Air Cleaner	Dual Stage Dry Type	
Block Heater	○	
Downdraft Exhaust Pipe	●	
Fuel Tank Capacity (l)	80	
TRANSMISSION		
12x12 Synchro Shuttle transmission	●	
Minimum/Maximum Speed	0.45 kmph/ 30 Kmph	
FRONT AXLE		
4WD Front Axle	●	
Differential Lock	Mechanical	
4WD Actuation	Mechanical 4WD	
Brake Actuation	Hydraulic Assisted Brakes	
PTO		
PTO Type	Mechanical	
540/540E	●	
HYDRAULIC		
Hydraulic pump flow (lpm)	45	
Open centre mechanical draft control	●	
Liftomatic system	●	
Lift Capacity (kg)	2500	
Linkage Category	II	
Self Locking TPL Linkages	○	
Max. no. of rear remotes	2/3 (O)	
REAR HITCHES		
E-Marked Swinging Bar	●	
CBM Ladder Hitch	○	
Cuna (X Type & Y Type) Hitch	○	
TRAILER BRAKES		
Without Trailer Brakes	●	
Hydraulic Trailer Brakes	○	



FEATURES		N75
ELECTRICALS (ROPS/CAB)		
Battery	130AH 800CCA	
Alternator	120A	
Button Operated Battery Cut off Switch, 3 Pin socket, Seven pin Trailer Socket	●	
OPERATOR ENVIRONMENT		
Suspended platform (with ROPS)	●	
Normal Driver seat w/o Armrest	●	
Tiltable & Telescopic Steering	●	
Integrated Loader Joystick	○	
Front Mud Guards	○	
Ballast Weights (31*6) Kg	○	
Ballast Rear Weights (30*2) Kg	○	
Cabin Air Conditioning (With HVAC)	○	
CAT IV cabin	○	
DIMENSIONS (ROPS/CAB)		
Wheelbase (mm)	2310	
Overall Length (mm)	4040 - 4280	
Overall Width (mm)	1400 - 1410	
Overall Height (mm)*	2330	
Front Track Width (mm)	1150 - 1210	
Rear Track Width (mm)	1000 - 1110	
Ground Clearance (mm)	260	
Unladen Mass (Kg)	3295	
STANDARD TYRES (ROPS/CAB)		
Bias Tyres (4WD)	8.00-18 & 14.9-24	
OPTIONAL TYRES (ROPS/CAB)		
Radial Tyres (4WD)	210/95R18 & 360/70R28	
	280/70R18 & 360/70R28	
	260/70R16 & 360/70R24	
	280/70R18 & 420/70R24	
	280/70R18 & 380/85R24	
	8x18 * 13.6X24	

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com