

# SOILS

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

**60**  
SHUTTLE XL



3 CYLINDER DIESEL  
ENGINE

12F+12R SYNCHROMESH  
SHUTTLE TRANSMISSION

HEAVY LIFT  
CAPACITY

EASY FRONT AND  
LOADER ATTACHMENT

HEAVY DUTY  
4WD



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

**THE TOUGHEST  
PERFORMER  
« FOR YOUR FIELD »**

**60  
SHUTTLE XL**

**Solis**



FEATURES	60 SHUTTLE XL
<b>ITL ENGINE</b>	
No. of Cylinders / Capacity (cc) / Emissions Level	3/ 3065/ CRDi Stage V
After Treatment System	DOC + DPF
Rated Engine Power (kw/Hp)	43.2/58
Rated Engine Speed	2000
Max. Torque (Nm)	250@1400 Rpm
Aspiration	Turbo Charged
Intercooler	●
Air Cleaner	Dual Stage Dry Type
Block Heater	○
Updraft Exhaust Pipe	●
Downdraft Exhaust Pipe	○
Fuel Tank Capacity (L)	72
<b>TRANSMISSION</b>	
12x12 Synchro Shuttle Transmission (4WD)	●
Minimum Forward Speed	1.3kmph
Maximum Forward Speed	30kmph
12x12 Synchro Shuttle Transmission (4WD) with Creeper	○
Minimum Forward Speed	0.5kmph
Maximum Forward Speed	30kmph
<b>FRONT AXLE</b>	
2WD Front Axle	○
4WD Front Axle	●
Differential Lock	Mechanical
4WD Actuation	Mechanical
Brake Actuation	Mechanical Assist
<b>PTO</b>	
PTO Type	Mechanical
540/540E	●
540/1000	○
540/ground speed	○
<b>HYDRAULIC</b>	
Hydraulic Pump Flow (LPM)	45
Open Center Mechanical Draft Control	●
Top Link Draft Sensing	●
Liftomatic System	○
Lift Capacity	2500 KG
Linkage Category	II
Self Locking Linkages	○
Max. no. of Rear Remotes	2/3 (Opt.)
Max. no. of Mid Remotes	2
Mechanical Joystick Control for Mid Mounts with Valves	1 (Opt.)
<b>REAR HITCHES</b>	
E-Mark Swinging Drawbar	●

FEATURES	60 SHUTTLE XL
Cuna Type Ladder Hitch	○
Semi Automatic Ladder Hitch	○
Automatic Ladder Hitch	○
<b>TRAILER BRAKES</b>	
Without Trailer Brakes	●
Hydraulic Trailer Brakes	○
Dual Line Pneumatic Trailer Brakes	○
<b>ELECTRICALS (ROPS/CAB)</b>	
Battery	110AH 800CCA
Alternator	90A/120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven on Trailer Socket	●
<b>OPERATOR ENVIRONMENT</b>	
Suspended platform (with ROPS)	●
Premium Driver Seat	○
Tiltable & Telescopic Steering	○
Integrated Loader Joystick	○
Cabin Air Conditioning (with Cabin)	○
<b>DIMENSIONS (ROPS/CAB)</b>	
Wheelbase (mm)	2225
Overall Height (mm)	ROPS: 2650 - 2700 CAB: 2450 - 2500
Overall Width (mm)	1825-1950
Overall Length (mm)	3830 - 4060
Front Track Width (mm)	1525 - 1570
Rear Track Width (mm)	1420 - 1440
Ground Clearance (mm)	310 - 355
Unladen Mass (Kg)	ROPS: 2780 - 3315 CAB: 3340 - 3560
Tyre Combination	9.5x24 & 14.9x28
<b>Optional Tyre Combinations</b>	
Bias Tyres (2WD)	7.5x16 & 16.9x28
Bias Tyres (4WD)	9.5x24 & 16.9x28
Radial Tyres (4WD)	250/85 R24 & 420/85 R28 280/85R24 AGRIMAX RT855 E 115A8/B SPL 420/85R28 AGRIMAX RT855 E 139A8/B SPL 320/70R24 AGRIMAX RT765 E 116D SPL 480/70R28 AGRIMAX RT765 E 140D SPL
Industrial Tyres (4WD)	10-16.5 & 14.9-24 12.5/80-18 & 18.4-24

● Standard ○ Optional

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

**DEALER STAMP**

**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com