

# SOiS

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

**75**  
SHUTTLE XL



4 CYLINDER STAGE V  
HIGH END TORQUE ENGINE

SYNCHRO SHUTTLE  
TRANSMISSION

ADVANCED HYDRAULIC  
LIFT CAPACITY

S COMMAND  
CENTER

MULTIPLE  
TYRE OPTIONS



**COST**  
EFFICIENT  
MECHANICAL TRACTORS

MADE OF  
**REAL**  
STEEL

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

# THE TOUGHEST PERFORMER « FOR YOUR FIELD »

**75**  
SHUTTLE XL

**Solis**



FEATURES	75 SHUTTLE XL
<b>ITL ENGINE</b>	
No. of Cylinders / Capacity (cc) / Emissions Level	4/ 4087/ CRDi Stage V
After Treatment System	DOC + DPF
Rated Engine Power (kw/Hp)	55.9/75
Rated Engine Speed	2000
Max. Torque (Nm)	340@1400 Rpm
Aspiration	Turbo Charged
Intercooler	●
Air Cleaner	Dual Stage Dry Type
Block Heater	○
Updraft Exhaust Pipe	●
Downdraft Exhaust Pipe	○
Fuel Tank Capacity (L)	88
DEF Tank Capacity (L)	-
<b>TRANSMISSION</b>	
12x12 Synchro Shuttle Transmission (4WD)	●
Minimum Forward Speed	1.22kmph
Maximum Forward Speed	35kmph
20x20 Synchro Shuttle Transmission (4WD) with Super Creeper	○
Minimum Forward Speed	0.25kmph
Maximum Forward Speed	40kmph
<b>FRONT AXLE</b>	
4WD Front Axle	●
Differential Lock	Mechanical
4WD Actuation	Electro Hydraulic
Brake Actuation	Hydraulic Assisted
<b>PTO</b>	
PTO Type	Mechanical
540/540E	●
540/1000	○
540/Ground Speed	○
<b>HYDRAULIC</b>	
Hydraulic Pump Flow (LPM)	65
Draft Control	●
Liftomatic System	●
Lift Capacity	2500 Kg / 3000 Kg (0)
Linkage Category	II
Self Locking Linkages	○
Max. no. of Rear Remotes	2/3 (0)
Max. no. of Mid Remotes	○
Mechanical Joystick Control for Mid Mounts with Valves	1 (0)
<b>REAR HITCHES</b>	
E-Mark Swinging Drawbar	●
Semi Automatic Ladder Hitch	○
Automatic Ladder Hitch	○

FEATURES	75 SHUTTLE XL
Cuna Type Ladder Hitch	○
<b>TRAILER BRAKES</b>	
Without Trailer Brakes	●
Hydraulic Trailer Brakes	○
Dual Line Pneumatic Trailer Brakes	○
<b>ELECTRICALS (ROPS/CAB)</b>	
Battery	130AH 800CCA
Alternator	ROPS: 90A / Cab: 120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven on Trailer Socket	●
<b>OPERATOR ENVIRONMENT</b>	
Suspended Platform (with ROPS)	●
Premium Driver Seat	○
Tilttable & Telescopic Steering	●
Integrated Loader Joystick	○
Cabin Air Conditioning (With Cabin)	○
<b>DIMENSIONS (ROPS/CAB)</b>	
Wheelbase (mm)	2350
Overall Height (mm)	ROPS: 2500 - 2730 Cab: 2490 - 2650
Overall Width (mm)	ROPS: 2000 - 2050 Cab: 2050 - 2080
Overall Length (mm)	ROPS: 4005 - 4230 Cab: 3915 - 4140
Front Track Width (mm)	1650-1850
Rear Track Width (mm)	1500-1700
Ground Clearance (mm)	300-420
Unladen Mass (Kg)	ROPS: 3550 - 3720 CAB: 3825 - 4245
Tyre Combination	11.2x24 & 16.9x30
<b>OPTIONAL TYRE COMBINATIONS</b>	
Bias Tyres (4WD)	12.4*24 18.4*30
Radial Tyres (4WD)	280/85R24 & 420/85R30 320/85R24 & 460/85R30 320/70R24 & 480/70R30 360/85R24 & 460/85R30

● Standard ○ Optional

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

**DEALER STAMP**



**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com